

## **DIGIT 100 White Matt R**

### **PRODUCT DESCRIPTION**

Flexible calendered monomeric PVC film 100 My, white matt, removable adhesive, laminated on a 120 g/m<sup>2</sup> one-sided clay-coated silicone paper liner.

Designed to be highly resistant to solvent aggression during printing process, when not exceeding the right concentration, and to guarantee very good printing performance on any solvent and eco-solvent based ink-jet printer.

Particularly suitable for application on flat surfaces.

<b>TECHNICAL CHARACTERISTICS:</b>	<b>Unit</b>	<b>Value</b>	<b>Tolerance</b>	<b>Test Method</b>
Face film: calendered monomeric PVC	mm	0,1	± 10%	ASTM D374
Total thickness	mm	0,12	± 10%	ASTM D374
Liner: one-sided clay-coated silicone paper	g/m <sup>2</sup>	120	± 10	ASTM D646
Adhesion on steel	N/''	5.5	± 1.5	AFERA 4001
Dimensional stability	mm	1	Maximum	FINAT FTM 14
Application temperature	°C	10 ÷ 40		
Service temperature	°C	-20 ÷ 50		
Outdoor duration of the unprinted film		3-5 years		

**SHELF LIFE:** Minimum 2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity .

**RECOMMENDATIONS FOR LAMINATING:** Please ensure the print is perfectly dry before laminating. We suggest to let the material dry for at least 48 hours after printing.

**STANDARD DIMENSIONS:** *Log 1050/1370/1550mm x 50m*